

Lanyards Webbing - L



Saferight manufactures a wide range of shock absorbing lanyards which are suitable for use in all situations. They are designed to limit the amount of force transferred onto the body in the event of a fall to 6kN.

Key Features

- Limits load to 6kN in the event of a fall
- Weight—all models are less than 1kg

Materials & Construction

- 25mm Green Webbing
- Alloy, mild steel or stainless steel hardware

Testing & Quality Control

- All lanyards meet the requirements of AS/NZS1891.1
- 100% Visual inspection
- Saferight is an ISO 9001 certified company

Options

CODE	LENGTH	PRODUCT DESCRIPTION
L06K5	0.6m	0.6m Fixed Lanyard with K5's
L06K1	0.6m	0.6m Fixed Lanyard with K1's
L06K19	0.6m	0.6m Fixed Lanyard with K1 and K9
L12K5	1.2m	1.2m Fixed Lanyard with K5's
L12K1	1.2m	1.2m Fixed Lanyard with K1's
L12K19	1.2m	1.2m Fixed Lanyard with K1 and K9
L2K5	2m	2m Fixed Lanyard with K5's
L2K1	2m	2m Fixed Lanyard with K1's
L2K19	2m	2m Fixed Lanyard with K1 and K9



Quality Endorsed Company
 ISO 9001
 QEC20205
 SAI Global



Australian Standard AS 1891.1 for Belts & Harnesses
 Licence No 1270

Head Office
 42 Belmont Avenue, Belmont, WA 6104
 Telephone: (08) 9334 1000 Facsimile: (08) 9334 1001
 Email: enquire@saferight.com.au

Queensland Office
 Unit 3, 605 Kingsford Smith Drive, Hamilton, QLD, 4007
 Telephone: (07) 3268 6900 Facsimile: (07) 3268 7288
 Email: enquireqld@saferight.com.au