

TRIPOD KIT—TRIPOD2/3



The Saferight tripod kit offers versatility and convenience for confined space entry and rescue applications, with an adjustable height from 1.7m to 3.0m.

There is a protected pulley built into the head of the tripod and the individual legs are rubber soled and are adjustable to cater for uneven surfaces. The tripod is commonly used in conjunction with the Fallright Rope Rescue System (FRS) or an Inertia Recovery Reel (IRR).

Key Features

- Adjustable height from 1.7m to 3.0m
- Legs have individual adjustability for use on uneven surfaces
- Feet can be rotated allowing spikes to push into the ground for extra stability when required
- Safe working load—2 persons
- Weight 33 kg
- Comes complete with rope and rope grab which can be attached to base to assist in sharing load evenly between legs and under load

Materials & Construction

- Extruded aluminium legs
- Aluminium head and feet
- 11mm Kernmantle rope and rope grab

Testing & Quality Control

- Proof loaded
- 100% visual inspection
- Individual serial numbered
- Saferight is an ISO 9001 Certified Company

Options

CODE	PRODUCT DESCRIPTION
TRIPOD2	Tripod 2m includes tripod carry bag
TRIPOD3	Tripod 3m includes tripod carry bag



Quality
Endorsed
Company
ISO 9001
QEC20205
SAI Global



Australian Standard
AS 1891.1 for
Belts & Harnesses
Licence No 1270

Head Office

42 Belmont Avenue, Belmont, WA 6104
 Telephone: (08) 9334 1000 Facsimile: (08) 9334 1001
 Email: enquire@saferight.com.au

Queensland Office

Unit 3, 605 Kingsford Smith Drive, Hamilton, QLD, 4007
 Telephone: (07) 3268 6900 Facsimile: (07) 3268 7288
 Email: enquireqld@saferight.com.au